



Baler RSA -98 High Speed		
	Package dimensions	
	Package cross-section size 46×36 cm	
1	Package length Adjustable from 30 to 130 cm	
	Pickup	
	Width inside opening 156 cm	
	Inlet width 175 cm	
	Distance between two end brackets 141 cm	
	Cylinder diameter 36 cm	
	Number of brackets 120 cm	
	Number of corner bracket holders 5	
	Compression piston	
	Length of the movement path 76 cm	1
	Speed 93 strokes per minute	
	Flywheel	
	Diameter 73 cm	
	Weight 135 Kg	
	Specifications of tractor used	2 000
	Minimum output power	TO THE
	in tractor's rear snait	
	Tractor rear shaft speed 540 rounds per minute	
	Gearbox volume	
	Amount of oil required 3.8 liters	
	Type of oil Gearbox oil 90	The same
	Tires	
	Right wheel tire 205/65-15	
	Left wheel tire 10/5-15	
	General dimensions of the machine	1
	Maximum machine height 175 cm	-

478 cm in moving position

1530 Kg

Machine length

Machine width

Machine weight

Ramesh Sanat Arak company, designed and distributed this baler in 8-2007 to meet the market demands and to rely on its own knowledge. In a short time, it has been able to find a place among distributors and consumers. Implementation of Product Tracking System, enables the company to examine and track all the machines it manufactures, after they are sold; and, the expert and consumers ideas about the products are used when necessary in order to ensure that the products distributed in the market are suitable for working in all agricultural conditions. One of the capabilities of this company is its competitiveness in both the regional and foreign markets with similar products; therefore, the products manufactured by this company are exported to Iraq, Tajikistan, Turkmenistan, Kazakhstan, and Armenia.

Based on studies on different countries and the importance of exports, this company has prototyped Baler RSA98 High Speed, and is now in the production stage.

Baler RSA98 is for export and its high speed is one of its advantages.



- 1- Hydraulic pickup lift
- 2- Feeding system with two high-capacity feeder forks
- 3- High maneuverability
- 4- Chain pickup transmission with clutch
- 5- 5reel pickup
- 6- Sending parts with the machine on costumer's request
- 7- Installation and training by after-sale service team in any region
- 8- For export
- 9- Ability to send 10 machines in containers to all parts of the world